

SPD 360 C+
SPD 360 CDH



3960 lbs



8'6" - 27'11"



6'11" - 11'2"

SPD360C+: 5280 lbs SPD360CDH: 5060 lbs		-	2T-D7: 22 lbs	JIB600M: 220 lbs	
	10'2"x2'7"x6'6"		SPD360C+: 0.62 MPH SPD360CDH: 1.12 MPH		20°
	4180 lbs		6.26 PSI		
SPD360C+					
	3kW 24V-DC SEP n°4 6V- 420 Ah				
SPD360CDH					
	Engine: 3 cylinders water cooled diesel, KUBOTA mod. D722-E3B, 2 rpm levels, EPA TIER 4 Motore: 3 cilindri diesel raffreddato a liquido, KUBOTA mod. D722-E3B, 2 livelli di regime, EPA TIER 4 Motor: Wassergekühlter 3 Zylinder Diesel Motor, KUBOTA mod. D722-E3B, 2 rpm, EPA TIER 4 Motor: Diesel 3 cilindros con refrigeración por aire, KUBOTA mod. D722-E3B, 2 niveles rpm, EPA TIER 4 Moteur: Diesel 3 cylindres, refroidissement à eau, KUBOTA mod. D722-E3B, accélérateur à 2 niveaux, EPA TIER 4				
	4kW 240V-60Hz-AC 1F		110 lbs		
Telescopic Boom: 1 base and 4 telescopic sections high-tensile structural steel. All sections synchronized and full power. Braccio Telescopico: 1 braccio principale e 4 telescopici in acciaio strutturale ad alta resistenza. Sfilo completamente idraulico e sincronizzato. Teleskopausleger: 1 Hauptausleger + 4 Hochwiderstand Stahl Teleskopausleger. Voll hydraulischer und teleskopierbarer Ausleger. Pluma Telescópica: 1 pluma principal y 4 telescópicas en acero de alta resistencia. Elementos sincronizados e hidráulicos. Flèche Téléscoquique: 1 flèche principale et 4 télescopiques en acier à haute résistance. Eléments synchronisés et hydrauliques.					
	360° 1.5 rpm		0°/70° 14"		
	6'11" - 27'11" 26"		1320 lbs - 196' - Ø5/16 in SPD360C+: 52 ft/min SPD360CDH: 45/90 ft/min		

