

SPX 527 CDH



5940 lbs



11'2" - 39'8"



6'11" - 13'5"

				
	7920 lbs	-	66 lbs	JIB600H: 484 lbs
 L x W x H	13'10"x3'7"x6'5"		1.24 MPH	 25°
 MAX	5940 lbs		6.68 PSI	
	Engine: 3 cylinders water cooled diesel, ISUZU mod. 3CB1, 2 rpm levels, EPA TIER 4 Motore: 3 cilindri diesel raffreddato a liquido, ISUZU mod. 3CB1, 2 livelli di regime, EPA TIER 4 Motor: Wassergekühlter 3 Zylinder Diesel Motor, ISUZU mod. 3CB1, 2 rpm, EPA TIER 4 Motor: Diesel 3 cilindros con refrigeración por aire, ISUZU mod. 3CB1, 2 niveles rpm, EPA TIER 4 Moteur: Diesel 3 cylindres, refroidissement à eau, ISUZU mod. 3CB1, accélérateur à 2 niveaux, EPA TIER 4			
 AUX	4kW 240V-60Hz-AC 1F		110 lbs	
Telescopic Boom: 1 base and 4 telescopic sections high-tensile structural steel. All sections synchronized and full power. Braccio Telescopico: 1 braccio principale e 4 telescopici in acciaio strutturale ad alta resistenza. Sfilo completamente idraulico e sincronizzato. Teleskopausleger: 1 Hauptausleger + 4 Hochwiderstand Stahl Teleskopausleger. Voll hydraulischer und teleskopierbarer Ausleger. Pluma Telescópica: 1 pluma principal y 4 telescópicas en acero de alta resistencia. Elementos sincronizados e hidráulicos. Flèche Télescopique: 1 flèche principale et 4 télescopiques en acier à haute résistance. Eléments synchronisés et hydrauliques.				
	360° 1 rpm		-2°/80° 35"	
	11'2" - 39'8" 40"		1980 lbs - 196' - Ø3/8 in SPX527CDH+: 98 ft/min	

